



PERFORMANCE DATA

PERFORMANCE-CFM AT STATIC PRESSURE SHOWN																			
Model No.	Motor HP	Motor Frame	Blower RPM	1" SP	1-1/2" SP	2" SP	2-1/2" SP	3" SP	3-1/2" SP	4" SP	5" SP	6" SP	7" SP	8" SP	9" SP	10" SP	11" SP	12" SP	dBA @ 5ft.
RA-4	1/3	56	3600	295	265	230	200	165	125	-	-	-	-	-	-	-	-	-	74
RA-5	1/3	56	3600	525	495	470	440	405	380	330	200	-	-	-	-	-	-	-	77
RA-6	1	56	3600	800	770	740	705	680	640	600	500	400	300	-	-	-	-	-	84
RA-7	3	145T	3600	1190	1160	1130	1100	1065	1030	1000	930	860	780	690	575	410	-	-	90
RA-8	5	184T	3600	2280	2230	2180	2130	2070	2020	1960	1840	1720	1570	1400	1240	1080	880	670	92

Note: Fan should not be run at static pressures less than shown in above table. Motor overload will result.



DIMENSIONS

Blower	Wheel	Bore	A	B	C	D	E	F	G	H	J	K	L	O	P	R	X	S	T	V	Ship Wt. +
RA-4	7-3/4x2-1/4	5/8	11	8	3	3	5	7	1/2	5-3/8	4-7/8	5-7/8	5-7/8	16	4	6-5/8	8-1/2	13-1/8	12	-	13 lbs.
RA-5	9x2-3/4	5/8	12-1/8	8	3-1/2	3-1/2	5-5/8	7	1/2	6-3/8	5-3/4	6-7/8	6-3/4	20-3/4	5	7-1/2	9-3/8	14-5/8	16	-	17 lbs.
RA-6	10-5/8x3	5/8	14-3/4	9	4	3-1/2	6-7/8	7-1/2	3/4	7-1/4	6-1/2	8	7-5/8	20-3/4	6	8-5/8	11-3/4	18-1/4	16	-	25 lbs.
RA-7	12-1/2x3	7/8	17	8	5	4	8	6-1/2	3/4	8-1/4	7-1/2	9	9-5/8	20-1/8	7	10	10-5/8	18-3/8	15	-	37 lbs.
RA-8	13-1/2x4-3/8	1-1/8	17-5/8	11-1/4	7-1/8	5-3/4	8	9-9/16	1	10-1/2	9-5/8	11-3/8	11	22	8	11-1/2	12-5/8	21-1/2	15	7-1/4	64 lbs.