

P-1V: Single Speed / Variable Speed Panel Mounted Fans



- Sturdily constructed direct drive, horizontal discharge fan.
- Durable powder coat finish.
- Standard heavy duty OSHA motor mount/guard.
- Motors are totally enclosed, ball bearing with overload protection.

Model P-1V : Panel Fans c/w OSHA Guard									
Leader Fan Number	Blade Dia.	RPM	H.P	Volts	CFM @ Static Pressure				Weight Lbs.
					0"	0.1"	0.125"	0.25"	
Single Speed/Variable Speed Fans									
P12-1V	12"	1700	1/4	115/230	1650	1560	1525	1400	23
P12-1VHE	12"	1450	1/15	115	1350	1290	1275	1150	19
P14-1V	14"	1700	1/4	115/230	2170	2030	1950	1900	25
P14-1VHE	14"	1450	1/15	115	1600	1525	1500	1300	21
P16-1V	16"	1700	1/4	115/230	2570	2470	2410	2260	26
P16-1VHE	16"	1450	1/15	115	1850	1750	1700	1550	22
P18-1V	18"	1700	1/4	115/230	3150	3000	2900	2575	31
P20-1V	20"	1700	1/3	115/230	3620	3420	3340	3120	34
P24-1V	24"	1700	1/3	115/230	5500	5400	5310	5100	37

MODEL - P-1V

Panel fan single / variable speed c/w OSHA guard

All dimensions are in inches.

MODEL #	A SQ.	B	Wall Opening
P12-1V	17	8	14
P12-1VHE	17	6 1/2	14
P14-1V	18 3/4	9	16
P14-1VHE	18 3/4	7 1/2	16
P16-1V	20 3/4	9	18
P16-1VHE	20 3/4	7 1/2	18
P18-1V	22 3/4	9	20
P20-1V	24 3/4	8 1/2	22
P24-1V	28 3/4	8 1/2	26

Standard Features

- Powder coated steel venturi
- Plated steel OSHA motor mount/guard
- Single or variable speed operation
- Aluminum fan blades on steel hub
- Totally enclosed motors

Accessories

- A - Disconnect switch
- B - Speed control
- C - Galvanized weather hood
- D - Front guard
- E - Thermostatic control
- F - Galvanized steel sleeve
- G - Aluminum backdraft damper
- H - Motorized aluminum backdraft damper
- I - Specials

