

P-3: Two Speed Panel Mounted Fans



- Sturdily constructed direct drive, horizontal discharge fan.
- Durable powder coat finish.
- Standard heavy duty OSHA motor mount/guard.
- Motors are totally enclosed, ball bearing with overload protection.

Model P-3: Panel Fans c/w OSHA Guard									
Leader Fan Number	Blade Dia.	RPM	H.P	Volts	CFM @ Static Pressure				Weight Lbs.
					0"	0.1"	0.125"	0.25"	
Two Speed Fans									
P8-3	8"	1600/1350	1/20	115	400/330	320/260	280/230	180/140	11
P10-3	10"	1600/1350	1/20	115	690/580	590/460	570/390	550/340	11
P12-3	12"	1725/1140	1/4	115	1670/1100	1600/950	1575/900	1450/625	24
P14-3	14"	1725/1140	1/4	115	2190/1440	2080/1325	2000/1300	1950/850	27
P16-3	16"	1725/1140	1/4	115	2580/1770	2480/1620	2430/1560	2270/1020	30
P18-3	18"	1725/1140	1/4	115	3200/2130	3050/2030	2950/1960	2625/1750	33
P20-3	20"	1725/1140	1/3	115	3640/2420	3440/2270	3360/2210	3140/1890	37
P24-3	24"	1075/860	1/3	115	5300/4240	5050/4040	4950/3960	4700/3760	41

MODEL - P-3

Panel fan 2 speed c/w OSHA guard

All dimensions are in inches.

MODEL #	A SQ.	B	Wall Opening
P08-3	14	7	12
P10-3	14	7	12
P12-3	17	8	14
P14-3	18 3/4	10 1/2	16
P16-3	20 3/4	10 1/2	18
P18-3	22 3/4	10 1/2	20
P20-3	24 3/4	11	22
P24-3	28 3/4	11	26

Standard Features

- Powder coated steel venturi
- Plated steel OSHA motor mount/guard
- 2 speed motor
- Aluminum fan blades on steel hub
- Totally enclosed motors

Accessories

- A - Disconnect switch
- B - 2 Speed switch
- C- Galvanized weather hood
- D - Front guard
- E - Thermostatic control
- F - Galvanized steel sleeve
- G- Aluminum backdraft damper
- H - Motorized aluminum backdraft damper
- I - Specials

