



DIMENSIONS

CAT. NO.	A	B	C	D
X8	14	11-1/4	6-3/4	7-1/2
X10				
X12	17	14		11-1/2
X14	18-3/4	15-3/4		
X16	20-3/4	17-3/4		
X18	22-3/4	19-3/4		
X20	24-3/4	21-3/4		12-1/4
X24	28-3/4	25-3/4		
X30	35-1/4	32-3/4	6	13
X36	41-1/4	38-3/4	6	10

PERFORMANCE DATA

CAT. NO.	FAN TYPE	FAN DIA.	HP	RPM	VOLTAGE	CFM				SOUND LEVEL	SHIP WEIGHT
						0"SP	.1"SP	.125"SP	.25"SP		
X8-3	2-SPEED	8"	1/40	1550/1300	115	360/300	270/150	230/110	-	48 dBA	12 lbs.
X10-3	2-SPEED	10"	1/40	1550/1300	115	690/580	590/460	570/390	-	56 dBA	13 lbs.
X12-1	STANDARD	12"	1/4	1725	115	1650	1540	1510	1390	63 dBA	28 lbs.
X12-2	LO-NOISE		1/3	1140	115	1090	950	930	-	50 dBA	32 lbs.
X12-3	2-SPEED		1/4	1725/1140	115	1650/1090	1540/950	1510/930	1390/-	64/50 dBA	32 lbs.
X12-VAR	VARI-SPEED		1/4	1625	115/230	1580	1480	1450	1340	60 dBA	32 lbs.
X14-1	STANDARD	14"	1/4	1725	115	2170	2070	2030	1860	67 dBA	30 lbs.
X14-2	LO-NOISE		1/3	1140	115	1350	1190	1160	-	53 dBA	34 lbs.
X14-3	2-SPEED		1/4	1725/1140	115	2180/1350	2080/1190	2060/1160	1890/-	65/53 dBA	34 lbs.
X14-VAR	VARI-SPEED			1/4	1625	115/230	2090	1990	1950	1780	64 dBA
X16-1	STANDARD	16"	1/4	1725	115	2570	2470	2410	2260	68 dBA	33 lbs.
X16-2	LO-NOISE		1/3	1140	115	1770	1620	1560	-	55 dBA	36 lbs.
X16-3	2-SPEED		1/4	1725/1140	115	2580/1770	2480/1620	2430/1560	2270/-	69/55 dBA	36 lbs.
X16-VAR	VARI-SPEED			1/3	1625	115/230	2470	2370	2320	2170	63 dBA
X18-1	STANDARD	18"	1/4	1725	115	3200	3090	3040	2920	73 dBA	37 lbs.
X18-2	LO-NOISE		1/3	1140	115	2100	1890	1820	-	64 dBA	43 lbs.
X18-3	2-SPEED		1/4	1725/1140	115	3200/2100	3090/1890	3040/1820	2920/-	74/64 dBA	43 lbs.
X18-VAR	VARI-SPEED			1/4	1625	115/230	3070	2970	2920	2810	71 dBA
X20-1	STANDARD	20"	1/3	1725	115	3620	3420	3370	3120	77 dBA	41 lbs.
X20-2	LO-NOISE			1140	115	2300	2000	1950	-	67 dBA	45 lbs.
X20-3	2-SPEED		1725/1140	115	3620/2300	3420/2000	3380/1950	3130/-	77/67 dBA	45 lbs.	
X20-VAR	VARI-SPEED			1625	115/230	3480	3280	3240	2990	76 dBA	45 lbs.
X24-1	STANDARD	24"	1/3	1625	115	5280	5190	5100	4890	77 dBA	49 lbs.
X24-2	LO-NOISE			1140	115	3650	3410	3290	-	67 dBA	53 lbs.
X24-3	2-SPEED		1100/800	115	3650/2920	3410/2728	3290/2630	-	67/64 dBA	53 lbs.	
X24-VAR	VARI-SPEED			1625	115/230	5280	5190	5100	4890	76 dBA	53 lbs.
X30-1	STANDARD	30"	1/2	1650	115/230	8000	7000	6000	5500	82 dBA	72 lbs.
X36-7	STANDARD	36"	1/2	850	115/230	12000	11000	10500	9500	72 dBA	88 lbs.